



2K SUPER-COMPACT

- TEMPERATUR RANGE** : -40°C (-40°F) to +100°C (+212°F)
- APPLICATION** : For High Pressure Hydraulic Systems Using Hydraulic Oils, Mineral And Vegetable Lubricants
- TUBE** : Mineral, Vegetable And Hydraulic Oil Resistant Special Synthetic Rubber
- REINFORCEMENT** : 2 High Tensile Steel Wire Braid
- COVER** : Oil, Abrasion And Weather Resistant Special Synthetic Rubber
- BRANDING** : Positive White
- 'SUNFLEX 2K EXCEEDS EN857 2SC'**

Hose Size					Max Working Pressure		Minimum Burst Pressure		Minimum Bend Radius	Hose Weight
Part Number	Dash	I.D.		O.D.	psi	bar	psi	bar	mm	m/kg
		inch	mm	mm						
2K-04-SF-S	-04	1/4	6.4	13.1	6525	450	28275	1950	45	0.285
2K-05-SF-S	-05	5/16	8.0	15.0	6090	420	25013	1725	60	0.330
2K-06-SF-S	-06	3/8	9.5	17.1	5583	385	23925	1650	70	0.440
2K-08-SF-S	-08	1/2	12.7	20.3	5003	345	20300	1400	90	0.565
2K-10-SF-S	-10	5/8	16.0	23.7	4205	290	17400	1200	130	0.660
2K-12-SF-S	-12	3/4	19.0	27.7	4060	280	17400	1200	160	0.835
2K-16-SF-S	-16	1	25.4	35.6	2900	200	13050	900	210	1.215