



BT600 GROUTING HOSE 600 PSI

Mandrel Built Rubber Hose Engineered For The Spraying Of Plaster, Grout, Gypsum And Concrete With A Heavy Construction Which Resists Kinking.

- Temperature Range** : -40°C (-40°F) to +85°C (+185°F)
- Tube** : Black, Smooth, Specially Compounded For Superior Resistance To Abrasion
- Reinforcement** : High Strength Synthetic Cord
- Cover** : Black, Smooth (Wrapped Finish) Abrasion, Weather And Ozone Resistant Synthetic Rubber
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : White Transfer Tape With Negative Text
'SUNFLEX BT600 GROUTING HOSE WPSI 600'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
BT600-0125	32	1-1/4	46	1-13/16	40	600	120	1800	320	1.10	0.75
BT600-0150	38	1-1/2	54	2-1/8	40	600	120	1800	380	1.50	1.03
BT600-0200	51	2	68	2-11/16	40	600	120	1800	508	2.20	1.51
BT600-0250	63	2-1/2	83	3-1/4	40	600	120	1800	630	3.26	2.23
BT600-0300	76	3	98	3-7/8	40	600	120	1800	762	3.71	2.54
BT600-0400	102	4	130	5-1/8	40	600	120	1800	1016	6.88	4.71