



WSD150-SP WATER SUCTION/DISCHARGE HOSE 150 PSI

Water Suction And Delivery Applications. It Is Recommended That This Hose Must Be Immersed Into Water After The Inside Of The Hose Is Filled Up. Otherwise, The Hose Floats On The Water Because Hose Weight Is Less Than Water.

- Temperature Range** : -30°C (-22°F) to +80°C (+176°F)
- Tube** : Black, Sea Water Resistance EPDM Rubber
- Reinforcement** : High Tensile Synthetic Cord Fabrics And Twin Embedded Helix Steel Wire. Helix Steel Wire Thickness Is 1.5mm Thicker Than Standard One
- Cover** : Black, Ozone, Weather And Abrasion And Sea Water Resistance EPDM Rubber
- Coils** : 7.6mt (25ft), 9.15mt (30ft) Continuous Length; Other Length Available On Request
- Branding** : Purple Transfer Tape With Negative Text
'SUNFLEX WSD 150 WATER SUCTION/DELIVERY HOSE WPSI 150 - SPECIAL'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Hose Weight		Bending Radius
	mm	inch	mm	inch	bar	psi	bar	psi	kg/m	lbs/ft	mm
WSD150-1000-SP	254	10	284	11-3/8	10	150	30	450	23.43	15.75	2032