



CSD150 CEMENT SUCTION HOSE 150 PSI

Dry Material Suction And Delivery Hose Specially Designed For Transfer Of Dry Cement, Sand, Gravel, Feed, Seeds etc By Suction, Gravity Or By Pneumatic Systems.

Temperature Range : -40°C (-40°F) to +85°C (+185°F)

Tube : Black, Smooth , Compounded For Long Wear Resistance In Handling Hard, Sharp, Abrasive Material; It Is Anti-Static

Reinforcement : High Strength Synthetic Cord Plus Helix Wire

Cover : Black, Smooth (Wrapped Finish) Synthetic Rubber, Weather, Ozone And Wear Resistant

Coils : 61mt (200ft) Continuous Length; Other Length Available On Request

Branding : Green Transfer Tape With Negative Text

'SUNFLEX CSD 150 BULK MATERIAL SUCTION/DELIVERY HOSE WPSI 150'

Part Number	I.D.		O.D.		Working Pressure		Bursting Pressure (Theoretical)		Bending Radius	Hose Weight	
	mm	inch	mm	inch	bar	psi	bar	psi	mm	kg/m	lbs/ft
CSD150-0300	76	3	98	3-55/64	10	150	30	450	456	2.90	1.92
CSD150-0400	102	4	124	4-7/8	10	150	30	450	612	4.67	3.11
CSD150-0500	127	5	152	5-63/64	10	150	30	450	762	5.80	3.90
CSD150-0600	152	6	174	6-27/32	10	150	30	450	900	10.10	6.25