



## SUNFLEX TWIN LINE WELDING HOSE Comply to EN 559

For Use With Welding And Allied Processes In Workshops, Shipyards, Construction Sites And Manufacturing Industries.

<b>Operating Temperature</b>	: -25°C To +75°C
<b>Tube</b>	: High Ignition Temperature Synthetic Rubber
<b>Reinforcement</b>	: High Tensile Synthetic Textile Filament Yarn
<b>Cover</b>	: Excellent Ozone And Weather Resistant Synthetic Rubber
<b>Color</b>	: [BLUE GREEN] - Oxygen / [RED] - Acetylene
<b>Surface</b>	: Ribbed
<b>Coils</b>	: 100mt Continuous Length
<b>Branding</b>	: Inkjet Black
	<b>'SUNFLEX WELDING HOSE - EN559 W/P 20 BAR B/P 60 BAR'</b>

Part Number	Nominal I.D.		O.D.	Working Pressure		Bursting Pressure	
	inch	mm	mm	psi	bar	psi	bar
WH-TWIN-0019	3/16	5.0 + 5.0	12.0 + 12.0	300	20	900	60
WH-TWIN-0025	1/4	6.0 + 6.0	13.0 + 13.0				
WH-TWIN-0025-0038	1/4 + 3/8	6.0 + 9.0	16.0 + 16.0				
WH-TWIN-0031	5/16	8.0 + 8.0	15.0 + 15.0				
WH-TWIN-0031-0038	5/16 + 3/8	8.0 + 9.0	16.0 + 16.0				
WH-TWIN-0038	3/8	10.0 + 10.0	17.0 + 17.0				