



MSD300 MULTI SUCTION/DISCHARGE HOSE 300 PSI

Heavy Duty Suction And Delivery Hose, Excellent For Use As A Tank Truck Or Tank Wagon Hose. It Withstands The Full Vacuum. Its Anti-static Cover Conforms Fully To PTB Specifications, Used For A Wide Range Of Petroleum Products Up To 50% Aromatic Content.

- Temperature Range** : -40°C (-40°F) to +100°C (+212°F)
- Tube** : Black, Smooth , Nitrile Rubber Compounded
- Reinforcement** : High Strength Synthetic Cord Plus Helix Wire And Anti-static Copper Wire
- Cover** : Black, Smooth (Wrapped Finish) High Grade Chloroprene Rubber, Compounded For An Excellent Resistance To Weather, Ozone, Abrasion And Oil Resistant; Anti-static
- Coils** : 61mt (200ft) Continuous Length; Other Length Available On Request
- Branding** : Purple Transfer Tape With Negative Text

'SUNFLEX MSD300 HEAVY DUTY OIL/WATER SUCTION DELIVERY HOSE WPSI 300'

| Part Number | I.D. | | O.D. | | Working Pressure | | Bursting Pressure (Theoretical) | | Bending Radius | Hose Weight | |
|-------------|------|-------|------|----------|------------------|-----|---------------------------------|-----|----------------|-------------|--------|
| | mm | inch | mm | inch | bar | psi | bar | psi | mm | kg/m | lbs/ft |
| MSD300-0200 | 51 | 2 | 65 | 2-9/16 | 20 | 300 | 60 | 900 | 250 | 1.98 | 1.32 |
| MSD300-0250 | 64 | 2-1/2 | 79 | 3-7/64 | 20 | 300 | 60 | 900 | 330 | 2.62 | 1.75 |
| MSD300-0300 | 76 | 3 | 93 | 3-21/32 | 20 | 300 | 60 | 900 | 420 | 3.40 | 2.28 |
| MSD300-0400 | 102 | 4 | 120 | 4-47/64 | 20 | 300 | 60 | 900 | 600 | 4.91 | 3.29 |
| MSD300-0500 | 127 | 5 | 149 | 5-7/8 | 20 | 300 | 60 | 900 | 750 | 7.15 | 4.79 |
| MSD300-0600 | 152 | 6 | 174 | 6-55/64 | 20 | 300 | 60 | 900 | 950 | 9.25 | 6.20 |
| MSD300-0800 | 203 | 8 | 230 | 9-1/16 | 20 | 300 | 60 | 900 | 1500 | 14.79 | 9.92 |
| MSD300-1000 | 254 | 10 | 288 | 11-19/64 | 20 | 300 | 60 | 900 | 1750 | 21.44 | 14.38 |
| MSD300-1200 | 306 | 12 | 343 | 13-1/2 | 20 | 300 | 60 | 900 | 2400 | 29.06 | 19.49 |