



OROFLEX 20

Color	: Yellow
Composition	: Synthetic Rubber And Polyester-Polyamide Textile
Surface	: Fine Ribbed, Highly Resistant To Abrasion
Service	: > From -20°C to +80°C
Standard Length	: 60m (Up To 200m To Order)

Part Number	I.D.		Wall Thickness	Air Service / Bursting Pressure	Traction Limit For No Tearing	Radius Of Curvature	Hose Weight
	mm	inch					
OF20-0075	19	3/4	2.5	20/160	300	0.250	0.180
OF20-0075	19	3/4	3.5	20/160	300	0.250	0.230
OF20-0100	27	1	3.5	20/100	750	0.250	0.235
OF20-0100	27	1	4	20/100	750	0.250	0.275
OF20-0150	38	1-1/2	3.5	15/75	1.200	0.650	0.440
OF20-0175	45	1-3/4	3.5	15/75	1.400	0.750	0.520
OF20-0200	52	2	3.5	10/50	1.500	1.200	0.650
OF20-0250	65	2-1/2	4	10/50	2.050	1.250	0.750
OF20-0300	76	3	4	10/50	2.600	1.300	0.950
OF20-0400	102	4	4	10/50	3.780	1.700	1.275
OF20-0500	127	5	4	10/50	5.980	1.970	1.800
OF20-0600	152	6	4	10/50	7.280	1.970	2.100
OF20-0800	204	8	4.5	10/50	9.320	2.250	2.550

**** In Yellow Version OROFLEX 20 HD Reinforced - To Order ****



- ◆ Contractor Air Hose
- ◆ High Pressure Pump Discharge
- ◆ Drilling Machine Compressor Hose
- ◆ Heavy Duty Dredge Discharge
- ◆ All Oroxflex-10 Applications Requiring A Heavier, Higher Pressure Hose
- ◆ Bulk Powder Discharge